



US009636837B2

(12) **United States Patent**
Kandemir

(10) **Patent No.:** **US 9,636,837 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **ANVIL ROLL SYSTEM AND METHOD**

(71) Applicant: **The Procter & Gamble Company**,
Cincinnati, OH (US)

(72) Inventor: **Mujdat Kandemir**, Cincinnati, OH
(US)

(73) Assignee: **The Procter & Gamble Company**,
Cincinnati, OH (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/517,950**

(22) Filed: **Oct. 20, 2014**

(65) **Prior Publication Data**

US 2015/0033926 A1 Feb. 5, 2015

Related U.S. Application Data

(62) Division of application No. 13/051,368, filed on Mar.
18, 2011, now Pat. No. 8,863,627.

(51) **Int. Cl.**

B26D 1/22 (2006.01)

B26D 3/08 (2006.01)

B26D 7/20 (2006.01)

B26D 7/26 (2006.01)

B26D 1/28 (2006.01)

B26F 1/38 (2006.01)

B26D 1/40 (2006.01)

(52) **U.S. Cl.**

CPC **B26D 7/204** (2013.01); **B26D 1/285**
(2013.01); **B26D 1/405** (2013.01); **B26D**
7/265 (2013.01); **B26D 1/40** (2013.01); **B26F**
1/384 (2013.01); **Y10T 83/0605** (2015.04);
Y10T 83/4838 (2015.04)

(58) **Field of Classification Search**

CPC B26D 7/204; B26D 1/405; B26D 1/40;
B26D 7/265; B26D 1/285; B26F 1/384;

Y10T 83/0605; Y10T 83/4838

USPC 83/56, 346, 13, 345, 660, 344, 669, 659,
83/658, 663

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,152,501 A 10/1964 Nassar
4,095,498 A 6/1978 Biggar, III
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 710 059 A1 10/2006
GB 2 273 287 A 6/1994

OTHER PUBLICATIONS

PCT/US2012/026209 PCT International Search Report, 7 pages.

Primary Examiner — Ghassem Alie

(74) *Attorney, Agent, or Firm* — Charles R. Matson

(57) **ABSTRACT**

The disclosure concerns a rotary cutting apparatus having a frame and a die roll defining a first longitudinal axis and having a cutting member. The die roll is rotatably connected with the frame and configured to rotate about the first longitudinal axis. The rotary cutting apparatus further has a bearer ring connected with the die roll and an anvil roll defining a second longitudinal axis and having an outer radial surface. The anvil roll is rotatably connected with the frame and is configured to rotate about the second longitudinal axis. The bearer ring of the die roll is in contact with the outer radial surface. The anvil roll may be supported by at least one cam follower. The anvil roll may be axially removable from the frame via lateral translation along the second longitudinal axis.

16 Claims, 9 Drawing Sheets

